

BraceCONDUIT, dzielony, BCA-D, poliamid PA6 V0



funkcje



BRACE



halogen



Zakres temperatury

-40 ° C - 140 ° C

Material

PA6 UL94-V0



Typ	Type	RAL-No.	NW	ED (mm)	Ø	Ugięcie	Waga
BCA-10-D-BK	BCA-10-D-BK	RAL 9005	10	12,9 mm	7,9 mm	60 mm	50 m
BCA-12-D-BK	BCA-12-D-BK	RAL 9005	12	15,8 mm	10,3 mm	75 mm	50 m
BCA-17-D-BK	BCA-17-D-BK	RAL 9005	17	21 mm	13,9 mm	85 mm	50 m
BCA-23-D-BK	BCA-23-D-BK	RAL 9005	23	28,3 mm	20,5 mm	130 mm	50 m
BCA-29-D-BK	BCA-29-D-BK	RAL 9005	29	34,5 mm	26,6 mm	140 mm	25 m
BCA-36-D-BK	BCA-36-D-BK	RAL 9005	36	41,8 mm	32 mm	160 mm	25 m
BCA-48-D-BK	BCA-48-D-BK	RAL 9005	48	54,2 mm	43 mm	170 mm	25 m



EU DECLARATION OF CONFORMITY



Product designation:	Plastic corrugated pipe
Type designation:	*(*)BF*(*)-**-**
Approval number:	deleted
Description:	Plastic corrugated pipe for electrical installations

corresponds to all the relevant provisions of the directives listed below and valid harmonized and / or international and national standards - including all applicable changes at this time of issuing this document.

Directive	Standard
2014/35/EU Electrical apparatus (Low voltage directive)	EN 61386-1:2008 + A1:2019 EN 61386-23:2004 + A11:2010
2014/34/EU Equipment and protective systems intended for use in potentially explosive atmospheres (ATEX)	Not applicable acc. to article 1, para. 1
2014/30/EU Electromagnetic compatibility (EMC directive)	Not applicable acc. to article 2, para. 2d)
2011/65/EU Use of certain hazardous substances (RoHS II)	EN IEC 63000:2018

2020-08-06


.....
Head of Development CAS

