



EMI/EMC small and large grommets

- ▶ Conductive grommets for cables from 2 to 35 mm diameter
- ▶ Single hole, multi-range, double and quadruple
- ▶ "Blind" version available
- ▶ UL94-HB
- ▶ Black color



Model	Code	Ø Cable [mm]	Pcs /pack	Model	Code	Ø Cable [mm]	Pcs /pack
SPP 0 EMC	1734024100	"blind"	10	SPG 0 EMC	1734024000	"blind"	10
SPP 2 EMC	1734024102	2-3		SPG 17 EMC	1734024117	17-18	
SPP 3-6 EMC	1734024140	3-6		SPG 18 EMC	1734024118	18-19	
SPP 6-9 EMC	1734024142	6-9		SPG 19 EMC	1734024119	19-20	
SPP 9-12 EMC	1734024144	9-12		SPG 20 EMC	1734024120	20-21	
SPP 12-15 EMC	1734024146	12-15		SPG 21 EMC	1734024121	21-22	
SPP 16 EMC	1734024116	16-17		SPG 22 EMC	1734024122	22-23	
SPP 2x2 EMC	1734024304	2 x 2	10	SPG 23 EMC	1734024123	23-24	10
SPP 2x3 EMC	1734024306	2 x 3		SPG 24 EMC	1734024124	24-25	
SPP 2x4 EMC	1734024308	2 x 4		SPG 25 EMC	1734024125	25-26	
SPP 2x5 EMC	1734024310	2 x 5		SPG 26 EMC	1734024126	26-27	
SPP 2x6 EMC	1734024312	2 x 6		SPG 27 EMC	1734024127	27-28	
SPP 2x7 EMC	1734024314	2 x 7		SPG 28 EMC	1734024128	28-29	
SPP 2x8 EMC	1734024316	2 x 8		SPG 29 EMC	1734024129	29-30	
SPP 4x2 EMC	1734024318	4 x 2	10	SPG 30 EMC	1734024130	30-31	10
SPP 4x3 EMC	1734024320	4 x 3		SPG 31 EMC	1734024131	31-32	
SPP 4x4 EMC	1734024322	4 x 4		SPG 32 EMC	1734024132	32-33	
SPP 4x5 EMC	1734024324	4 x 5		SPG 33 EMC	1734024133	33-34	
SPP 4x6 EMC	1734024326	4 x 6		SPG 34 EMC	1734024134	34-35	

The EMC grommets allow several shielded cables from 2 to 35 mm diameter to be routed in the DES EMC splittable frame.

The contact between the cable sheath and the grommet is safe and wide thanks to the grommet thickness.

The multi-range grommets simplify the cable shielding application and conductive element adhesion.

Technical data

Material: TPE with conductive element

Flammability: self-extinguishing acc. to UL94-HB

Temperature: -40°C... +100°C (static)

Features: halogens and silicones free

Related products

DES EMC