







Cechy



Klasa ochrony	IP68 / IP69
Zakres temperatury	-40°C - 100°C
Materiał	Dławik Poliamid, Uszczelka TPE, Membrana ePTFE

Typ	RAL-No.				TL (mm)	
ADOP 12 G	RAL7035	8 mm	M12x1,5	16 mm	17,4 mm	10
ADOP 20 G	RAL7035	9 mm	M20x1,5	24 mm	15,4 mm	10
ADOP - L 20 G	RAL7035	15 mm	M20x1,5	24 mm	21,4 mm	10
ADOP 40 G	RAL7035	9 mm	M40x1,5	46 mm	15,4 mm	10
ADOP - L 40 G	RAL7035	18 mm	M40x1,5	46 mm	24,4 mm	10
ADOP 12 B	RAL9005	8 mm	M12x1,5	16 mm	17,4 mm	10
ADOP 20 B	RAL9005	9 mm	M20x1,5	24 mm	15,4 mm	10
ADOP - L 20 B	RAL9005	15 mm	M20x1,5	24 mm	21,4 mm	10
ADOP 40 B	RAL9005	9 mm	M40x1,5	46 mm	15,4 mm	10
ADOP - L 40 B	RAL9005	18 mm	M40x1,5	46 mm	24,4 mm	10

